

Listing of the Claims

1. (Original) A method of planning a radiation therapy, the method comprising the steps of:

determining a dose distribution for a target volume on the basis of a first image;
determining at least one of shape and position variation of an object of interest in the target volume between the first image and a second image; and
adjusting the dose distribution on the basis of the at least one of shape and position variation;
wherein the first and second images were taken at different points in time of a radiation treatment process.

2. (Original) The method of claim 1, further comprising the steps of:

applying a first surface mesh to the object of interest in the first image;
performing a first adaptation of the first surface mesh to a surface of the object of interest in the first image resulting in a second surface mesh;
applying the second surface mesh to the object of interest in the second image;
performing a second adaptation of the second surface mesh to the surface of the object of interest in the second image resulting in a third surface mesh; and
obtaining a difference between the second surface mesh and the third surface mesh.

3. (Original) The method of claim 2 further comprising the steps of:

generating a volumetric model of the object of interest on the basis of the second surface mesh; and
deforming the volumetric model on the basis of the difference resulting in a deformed volumetric model.

4. (Original) The method of claim 3,

wherein the difference is used as a boundary condition for the deformation of the volumetric model.

5. (Original) The method of claim 3,

wherein the at least one of shape and position variation of the object of interest is determined on the basis of the deformed volumetric model.

6. (Original) The method of claim 3,

wherein a biomechanical model is taken into account for the deformation of the volumetric model.

7. (Original) The method of claim 1, wherein the first and second images are computed tomography (CT) images.

8. (Currently Amended) A radiation therapy planning device, comprising:

a memory for storing a first image and a second image; and
a processor ~~adapted to perform the steps of~~for:

determining a dose distribution for a target volume on the basis of the first image;

determining at least one of shape and position variation of an object of interest in the target volume between the first image and the second image; and

adjusting the dose distribution on the basis of the at least one of shape and position variation;

wherein the first and second images were taken at different points in time of a radiation treatment process.

9. (Currently Amended) The radiation therapy planning device of claim 8, ~~wherein the further comprises a processor is further adapted to perform the steps of~~for:

applying a first surface mesh to the object of interest in the first image;

performing a first adaptation of the first surface mesh to a surface of the object of interest in the first image resulting in a second surface mesh;

applying the second surface mesh to the object of interest in the second image;

performing a second adaptation of the second surface mesh to the surface of the object of interest in the second image resulting in a third surface mesh;

obtaining a difference between the second surface mesh and the third surface mesh;

generating a volumetric model of the object of interest on the basis of the second surface mesh; and

deforming the volumetric model on the basis of the difference resulting in a deformed volumetric model.

10. (Original) The radiation therapy planning device of claim 9,

wherein the difference is used as a boundary condition for the deformation of the volumetric model; and

wherein a biomechanical model is taken into account for the deformation of the volumetric model.

11. (Original) A computer program for a radiation therapy planning device,

wherein a processor of the radiation therapy device performs the following operation when the computer program is executed on the processor:

determining a dose distribution for a target volume on the basis of a first image;

applying a first surface mesh to the object of interest in the first image;

performing a first adaptation of the first surface mesh to a surface of the object of interest in the first image resulting in a second surface mesh;

applying the second surface mesh to the object of interest in the second image;

performing a second adaptation of the second surface mesh to the surface of the object of interest in the second image resulting in a third surface mesh;

obtaining a difference between the second surface mesh and the third surface mesh;

generating a volumetric model of the object of interest on the basis of the second surface mesh;

deforming the volumetric model on the basis of the difference resulting in a deformed volumetric model; and

adjusting the dose distribution on the basis of the deformed volumetric model;

wherein the first and second images were taken at different points in time of a radiation treatment process.

12. (New) The method of claim 2, wherein the second surface mesh and the third surface mesh result from applying the same surface model.

13. (New) The radiation therapy planning device of claim 9, wherein the second surface mesh and the third surface mesh result from applying the same surface model.

14. (New) A method for adapting a dose distribution of a radiation therapy plan comprising:

adapting a first surface mesh to an object of interest in a first image;
adapting a second surface mesh to the object of interest in a subsequent image;
deforming a volumetric model of the object of interest based on a difference between the first and second surface meshes.

15. (New) The method of claim 14, wherein the subsequent image is acquired prior to a radiation therapy treatment.

16. (New) The method of claim 14, wherein the subsequent image is acquired prior to a predetermined interval of radiation therapy treatments.